Brickcom

1.3 Megapixel Outdoor Bullet Network Camera

OB-130Af

Cost Effective / High Resolution

- Most Intelligent, Compact and Affordable 1.3M Outdoor Bullet Camera
- Cost Effective/ High Resolution/ Full Features Camera
- HDTV Quality (720p @ 30fps Streaming)
- **Intelligent Multi-Profile Sensor Management®** for Different Environments
- Removable IR-cut Filter /Auto Light Sensor for Day and Night
- Unique Design for Low Lux Application (1/2.5” Sensor)
- Built-in Micro SD/SDHC Memory Card Slot for Local Storage
- IP66 Outdoor Enclosure
- 1 DI/DO for External Alarm and Sensor Device
- Power over Ethernet

Photo Indication & Dimension Diagram

1. IR LED(35pcs)
2. Lens
3. Light Sensor
4. RJ45 Connector 1 (For Ethernet and PoE 802.3 af)
5. Power Connector (DC12V)
6. Ground
7. Audio Signal
8. Audio Out Ground
9. RS485-
10. RS485+
11. Digital In
12. Digital Out
13. Audio In
14. Audio In Ground
15. 5V





Camera

Hardware System	CPU: 533 MHz Flash: 32M RAM: 256M DDR
Image Sensor	Sensor Type : 1/2.5" CMOS Sensor Sensor Resolution : 1280 x 1024 pixel
Minimum Illumination	0 lux (IR ON, B/W) 2 lux (F1.6, Color)
IR Illuminators	Built –In IR Illuminators, effective up to 20 meters IR LED:35pcs(850nm)
Day and Night	Removable IR-cut Filter /Auto Light Sensor for Day and Night
Local Storage	Built-in Micro SD/SDHC Memory Card Slot

Video

Compression Streaming	H.264 / MPEG4 / MJPEG Simultaneous multiple streams
Video Setting	Multi-Profile Sensor Management Day/ Night / Sunset/ User 1/ User 2 Auto Exposure / Gain / White Balance Control Manual Exposure Control:1/20000~1/5s Manual Gain Control: 1X~32X Manual White Balance Control: 2000K~7000K
S/N Ratio	38.1dB
Image Resolution	**1.3M :** 1280 x1024 @ 30fps **1M (HDTV):** 1280x720 @ 30fps

Product Distinction



Events and Alarm Management

Events	Motion Detection Digital Input Schedule Audio Detection
Alarm	Stream/Snapshot to FTP/Email/Samba/SD-Card Activate Digital Output HTTP/Email Notification Audio Notification

Audio

Audio Streaming	2-way Audio Support
Audio Compression	G.711, AMR (8 kHz, Mono, PCM)
Audio Input/ Output	Line in/ Line out

General

Communication	Ethernet : one 10/100Mbps RJ-45 Supported Protocols : TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, RTP, RTSP, RTCP, IPv6
Power Input	DC12V/ 1A(Power Supply)/PoE 802.3af
Max. Power Consumption	8 watts
Environment	Operating Temperature: -20°C ~ 50°C(-4°F ~122°F) Operating Humidity : 10% ~ 80%
Dimension	288.6 (L) 122.9 (W) X 127.5 (H) mm
Weight	Net: 658g/1.45lb
Housing	Weather-proof IP66
Certification	FCC, CE
Viewing System Requirements	OS: Microsoft Windows 7/Vista/XP/2000 Browser: Mozilla Firefox, Internet Explorer 6/7 or above, Safari, Google Chrome Cell Phone: 3GPP player Real Player: 10.5 or above Quick Time: 6.6 or above VLC
Warranty	Limited One-year warranty

Lens Spec

OB-130Af	f=4mm	f=6mm	f=8mm
Lens Type	Board Lens	Board Lens	Board Lens
F Number	F=1.6	F=1.6	F=1.6
FOV(H/V/D)	50°/40°/61°	40°/22°/46°	30°/16°/34°

Work Best With

Network Equipment Options

POE 16U
PoE Injector

PS-588I
8-port 10/100M PoE Fast Ethernet Switch

PS-7242IL-AF
24-port 10/100M PoE Web Smart Ethernet Switch

Copyright© 2012 Brickcom Corporation. All rights reserved. All other company names and products are trademarks or registered trademarks of their respective companies. We reserve the right to introduce modifications without notice.

Brickcom
info@brickcom.com